

# SAFETY DATA SHEET

## 1. Identification

Product identifier	CGC Sheetrock® Brand Total™ Drywall Compound	
Other means of identification		
SDS number	61001010021	
Synonyms	Joint Compound (Ready-Mixed), Taping Compound, Mud, Finishing Compound	
Recommended use	Interior use.	
Recommended restrictions	Use in accordance with manufacturer's recommendations.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	CGC Inc.	
Address	350 Burnhamthorpe Road West, 5th Floor	
	Mississauga, Ontario L5B 3J1	
	A Subsidiary of USG Corporation	
Telephone	1-800-387-2690	
Website	www.cgcinc.com	
Emergency phone number	1-800-507-8899	
2. Hazard(s) identification		
Physical hazards	Not classified.	
Health hazards	Not classified.	
Environmental hazards	Not classified.	
Label elements		
Hazard symbol	None.	
Signal word	None.	
Hazard statement	None.	
Precautionary statements		
Prevention	Observe good industrial hygiene practices.	
Response	Get medical attention/advice if you feel unwell.	
Storage	Store as indicated in Section 7.	
Disposal	Dispose of in accordance with federal, provincial and local regulations.	
Other hazards	None known.	
Supplemental information	Not applicable.	

# 3. Composition/information on ingredients

#### Mixtures

Chemical name		CAS number	%
Perlite		93763-70-3	< 15
Kaolin		1332-58-7	< 10
Attapulgite		12174-11-7	< 5
Composition comments	All concentrations are in percent by weight unless ingredient is a gas. Raw materials in this product contain respirable crystalline silica as an impurity. Independent, third party industrial hygiene testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL (which is equivalent to the Quebec OEL of 0.05 mg/m3). However, actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing.		
4. First-aid measures	Dust irritates the respiratory system, and ma injured person into fresh air and keep person symptoms persist.		

Skin contact	Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.
Eye contact	Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Under normal conditions of intended use, this material does not pose a risk to health. Dust may irritate throat and respiratory system and cause coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved.
5. Fire-fighting measures	
Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not applicable.
Specific hazards arising from the chemical	Not a fire hazard.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials.
Specific methods	Cool material exposed to heat with water spray and remove it if no risk is involved.
General fire hazards	No unusual fire or explosion hazards noted.
6. Accidental release meas	sures
Personal precautions, protective equipment and	See Section 8 of the SDS for Personal Protective Equipment.

Personal precautions, protective equipment and emergency procedures	See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, provincial, and federal regulations.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Avoid discharge to drains, sewers, and other water systems.
7. Handling and storage Precautions for safe handling	Avoid inhalation of dust and contact with skin and eyes. Minimise dust generation and

Precautions for safe handling
Avoid inhalation of dust and contact with skin and eyes. Minimise dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.
Conditions for safe storage, including any incompatibilities
Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a mouldy appearance or an unpleasant odour. Keep containers closed when not in use.

Filled cartons and pails of joint compound may be stacked a maximum of 3 layers high on a pallet. Pallets may only be stacked a maximum of two high.

# 8. Exposure controls/personal protection

## Occupational exposure limits

## **US. ACGIH Threshold Limit Values**

Туре	Value	Form
TWA	2 mg/m3	Respirable fraction.
onal Health & Safety Code, Sch	nedule 1, Table 2)	
Туре	Value	Form
•	TWA	

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.
Canada. Manitoba OELs (F	Reg. 217/2006, The Workplace Safety A	nd Health Act)	
Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Canada. Ontario OELs. (Co	ontrol of Exposure to Biological or Che	mical Agents)	
Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Perlite (CAS 93763-70-3)	TWA	10 mg/m3	
Canada. Quebec OELs. (M	inistry of Labour - Regulation Respecti	ng the Quality of the Work I	Environment)
Components	Туре	Value	Form
Attapulgite (CAS 12174-11-7)	TWA	1 fibers/cm3	Fiber.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted for	the ingredient(s).	
propriate engineering htrols	Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimise the risk of exposure.		
ividual protection measures Eye/face protection	s, such as personal protective equipme Wear approved safety goggles.	nt	
Skin protection			
Hand protection	It is a good industrial hygiene practice to minimise skin contact. For prolonged or repeated skin contact use suitable protective gloves.		
Other	Normal work clothing (long sleeved shirts and long pants) is recommended.		
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure air supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.		
Thermal hazards	None.		
neral hygiene nsiderations	None. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.		

## 9. Physical and chemical properties

Appearance	
Physical state	Semi-solid.
Form	Paste.
Colour	Off-white.
Odour	Low to no odour.
Odour threshold	Not applicable.
рН	9.5 - 9.9
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.

## Upper/lower flammability or explosive limits

Upper/lower flammability or explosive limits			
Not applicable.			
0.9 - 1 (H2O=1)			
Soluble in water.			
Not applicable.			
0.9 - 1 kg/l			
4 g/l			

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.	
Chemical stability	Material is stable under normal conditions.	
Possibility of hazardous reactions	Hazardous polymerisation does not occur.	
Conditions to avoid	None known.	
Incompatible materials	None known.	
Hazardous decomposition products	Above 800°C (1472°F) limestone (CaCO3) can decompose to lime (CaO) and release carbon dioxide (CO2).	

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	Airborne dust may irritate throat and upper respiratory system causing coughing.
Skin contact	May cause allergic skin reactions especially in individuals with pre-existing skin disease such as eczema. (See Section 16).
Eye contact	Airborne dust may cause mechanical eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing.

#### Information on toxicological effects

Acute toxicity

Not expected to be a hazard under normal conditions of intended use.
--

,	•	
Components	Species	Test results
Kaolin (CAS 1332-58-7)		
Acute		
Dermal		
LD50	Rat	> 5000 mg/kg
Inhalation		
LC50	Rat	> 2 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation	Prolonged or repeated skin contact may cause drying, cracking, or irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitisation	n		
<b>Respiratory sensitisation</b>	Not a respiratory sensitiser.		
Skin sensitisation	The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact. For detailed information, see section 16.		
Germ cell mutagenicity	Data does not suggest that this product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not expected to increase the risk of cancer.		
ACGIH Carcinogens			
Kaolin (CAS 1332-58-7)		A4 Not classifiable as a human carcinogen.	
Canada - Manitoba OELs: ca	arcinogenicity		
KAOLIN, RESPIRABLE FRACTION (CAS 1332-58-7) Canada - Quebec OELs: Carcinogen category		Not classifiable as a human carcinogen.	
Attapulgite (CAS 12174-11-7)		Detected carcinogenic effect in humans.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity		
Attapulgite (CAS 12174-1	11-7)	2B Possibly carcinogenic to humans. 3 Not classifiable as to its carcinogenicity to humans.	
Reproductive toxicity	Not expected to be a reproductive hazard.		
Specific target organ toxicity - single exposure	No data available, but none expected.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged exposure may cause chronic effects. For detailed information, see section 16.		
Further information	No additional adverse health effects noted.		

## 12. Ecological information

#### Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

			5 5
Components		Species	Test results
Kaolin (CAS 1332-58-7)			
Aquatic			
Acute			
Crustacea	LC50	Daphnia magna	> 1.1 g/l, 48 Hours
sistence and degradability	No data available.		
accumulative potential	Bioaccumulation is not expected.		
bility in soil	No data available.		
ner adverse effects	None expected.		

## 13. Disposal considerations

Disposal instructions	Dispose of in accordance with federal, provincial and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Not regulated.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

## 14. Transport information

## TDG

Not regulated as dangerous goods.

## ΙΑΤΑ

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

### 15. Regulatory information

**Canadian regulations** 

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

## Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

**Precursor Control Regulations** 

Not regulated.

## International regulations

**Stockholm Convention** 

- Not applicable. Rotterdam Convention
- Not applicable.
- Kyoto protocol
- Not applicable.
- Montreal Protocol

Not applicable.

**Basel Convention** 

Not applicable.

## 16. Other information

Issue date	02-Mav-2016
Revision date	07-May-2024
Version No.	02
Further information	Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human exposure per ACGIH.
	Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.
	Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Independent, third party industrial hygiene testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL (which is equivalent to the Quebec OEL of 0.05 mg/ m3). However, actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing.
	Bucket NFPA Classification: Health: 0 Flammability: 1 Physical hazard: 0
NFPA ratings	Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe Health: 1 Flammability: 0 Instability: 0



List of abbreviations	ACGIH: American Conference of Governmental Industrial Hygienists. NFPA: National Fire Protection Association. RTECS: Registry of Toxic Effects of Chemical Substances.
References	Registry of Toxic Effects of Chemical Substances (RTECS) HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity Torben et al. (2001). Environmental and Health Assessment of Substances in Household Detergents and Cosmetic Products.
Disclaimer	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.