

Declare.

Securock® ExoAir® 430 Air Barrier System with Spectrem® 1 Silicone Sealant United States Gypsum Company

Final Assembly: Jacksonville, Florida, USA

Life Expectancy: 30+ Year(s)

End of Life Options: Landfill (100%)

Ingredients:

Securock® ExoAir® 430 Panel: Calcium sulfate dihydrate; Calcium carbonate; 2-Propenoic acid, butyl ester, polymer with 2-propenenitrile; Fiberglass; Magnesium oxide (MgO); Metaphosphoric acid (H3P3O9), trisodium salt; Poly(methylhydrosiloxane); Zinc oxide; Carbonic acid, magnesium salt (1:1); Zirconate(2-), bis[carbonato(2-)-O]dihydroxy-, diammonium, (T-4)-; Quartz; Cellulose, 2-hydroxyethyl ether; **Spectrem® 1 Silicone Sealant:** Calcium carbonate; Proprietary 1 (0.01-0.05%)¹; Proprietary 2 (0.01-0.05%)¹

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|------------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99.9% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

USG-0066

EXP. 01 JAN 2022

Original Issue Date: 2019